

BILTON AIR SIDE PLUS 600

BLAIRSP0600024DC13867840000W01

Article no.: 101951



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

BILTONAIR SIDE+ 600 LED strip 24VDC 13,8W/m IP67 CRI>80 4000K WHITE 1m LED module BILTON AIR SIDE PLUS 600 Article 101951 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from at a service life of . The BILTON AIR SIDE PLUS 600 LED-strip has a luminous flux of 610 at 13.8 , resulting in an efficiency of . At a nominal voltage of 24 DC on the connection, a maximum module length of 5010 can be achieved. In terms of lighting, the module has a colour temperature of 4000 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of . Degree of protection IP67 Smallest possible bending radius 200 Dimension (L x W x H): 1010 x 13.2 x 16

TOP-FEATURES

- //__ Homogeneously illuminated light line with no visible light points
- //__ IP67 protection in highly flexible silicone jacket
- //__ Unlimited freedom of design (flexibly deformable and separable)



BILTON AIR SIDE PLUS 600

BLAIRSP0600024DC13867840000W01

Article no.: 101951



MECHANICAL DATA

Width	13.2
Length	1010
Height/depth	16
Height	16
Colour	White
Model	Schlauch
Self-adhesive	nein
Lamp type	LED nicht austauschbar
Degree of protection (IP)	IP67
Length of particular segments	50
Lowest bending radius	200
With connection set	yes
With end piece	yes
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Lamp power per meter	13.8

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Colour temperature	4000
Luminous flux per meter	610

CONNECTION

Max. length	5010
-------------	------

PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054039
Gross width [mm]	330
Gross height [mm]	27
Gross length [mm]	330
Net width [mm]	13.2
Net height [mm]	16
Net length [mm]	1010

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (w/ Ra90). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

BLAIRSP0600024DC13867840000W01

Article no.: 101951

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

