




BILTON AIR TOP PLUS 600

BLAIRTP0600024DC07567827000W05

Article no.: 101912



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

BILTONAIR TOP+ 600 LED strip 24VDC 7,5W/m IP67 CRI>80 2700K WHITE 5m LED module BILTON AIR TOP PLUS 600 Article 101912 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 50000 . The BILTON AIR TOP PLUS 600 LED-strip has a luminous flux of 570 at 7.5 , resulting in an efficiency of 76 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a colour temperature of 2700 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP67 Smallest possible bending radius 200 Dimension (L x W x H): 5010 x 13.2 x 12

TOP-FEATURES

- //_ Homogeneously illuminated light line with no visible light points
- //_ IP67 protection in highly flexible silicone jacket
- //_ Unlimited freedom of design (flexibly deformable and separable)



BILTON AIR TOP PLUS 600

BLAIRTP0600024DC07567827000W05

Article no.: 101912



PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054039
Net weight [g]	0.609
Gross weight [g]	0.609
Gross width [mm]	330
Gross height [mm]	27
Gross length [mm]	330
Net width [mm]	13.2
Net height [mm]	12
Net length [mm]	5010

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at