


BLECP 600

BLECP0600024DC05320827000W05


Article no.: 170994



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

BL ECO+ 600 LED strip 24VDC 5,3W/m IP20 CRI>80 2700K WHITE 5m LED module BLECP 600 Article 170994 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BLECP 600 LED-strip has a luminous flux of 540 at 5.3 , resulting in an efficiency of 101 . At a nominal voltage of 24 DC on the connection, a maximum module length of 21500 can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 8.3 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 x 1.2

TOP-FEATURES

- //__ Long line lengths and better stability due to double layer
- //__ Guaranteed LED properties with guaranteed patent protection
- //__ Current regulation via transistors
- //__ To create a homogeneous light image, the band is populated with ###attribute.6040### LEDs per meter



BLECP 600

BLECP0600024DC05320827000W05

Article no.: 170994



MECHANICAL DATA

| | |
|-------------------------------|------------------------|
| Width | 8 |
| Length | 5000 |
| Height/depth | 1.6 |
| Height | 1.2 |
| Colour | White |
| Model | Band |
| Self-adhesive | yes |
| Lamp type | LED nicht austauschbar |
| Distance | 8.3 |
| Distance relating to | LED zu LED |
| Degree of protection (IP) | IP20 |
| Length of particular segments | 50 |
| Lowest bending radius | 20 |
| With connection set | yes |
| With end piece | nein |
| Number of lamps per meter | 120 |

ELECTRICAL DATA

| | |
|----------------------|------|
| Protection class | ohne |
| Voltage type | DC |
| Lamp voltage | 24 |
| Lamp power per meter | 5.3 |
| Overall efficiency | 101 |

LIGHT TECHNICAL DATA

| | |
|---|-------|
| Beam angle | 120 |
| Colour rendering index CRI | >80 |
| Colour temperature [K] | 2700 |
| Colour of light | White |
| Luminous flux per meter | 540 |
| Energy efficiency class provided exchangeable built-in lamp | F |
| Colour consistency (McAdam ellipse) | SDCM3 |

CONNECTION

| | |
|-------------------------|-------|
| Conductor cross section | 0.5 |
| Number of poles | 2 |
| Max. length | 21500 |

TEMPERATURE TECHNICAL DATA

| | |
|--------------------------------------|---------------|
| Ambient/storage temperature | - 5 ... + 55 |
| Operation temperature at Tc | - 5 ... + 60 |
| Ambient temperature during operating | - 20 ... + 45 |
| Rated life time L70/B50 at 25 °C | 60000 |

BLECP 600

BLECP0800024DC05320827000W05

Article no.: 170974



PACKAGING INFORMATION

| | |
|-----------------------|----------|
| State of origin | CN |
| Customs tariff number | 94054239 |
| Net weight [g] | 9.8 |
| Gross weight [g] | 35 |
| Gross width [mm] | 200 |
| Gross height [mm] | 18 |
| Gross length [mm] | 200 |
| Net width [mm] | 8 |
| Net height [mm] | 1.6 |
| Net length [mm] | 1000 |

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at