DALI LC Gateway

BLGATTOU024DC03DALI06420
Article no.: 101669

BETTER LIGHT



DALI

Control signal

TENDER TEXT

BILTON GATEWAY TOUCH 12-48VDC DIN-rail DALI 64TN IP20 BILTON LEDON TechnologyDALI LC Gateway Article 101669 The controller DALI LC Gateway is operated with DALI and is served with a sonstige . The controller and has an output voltage of 24 .The power dissipation in stand-by is . Dimension (L x W x H): 105 x 85 x 59

TOP-FEATURES

//__ Freely programme and control 64 addresses, 16 scenes and 16 groups by iPhone/iPad

//__ Activation takes place directly via iPhone/iPad

//__ Integration into an existing network or WLAN

DALI RoHS COMPLIANT 2002/95/EC CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

DALI LC Gateway

BLGATTOU024DC03DALI06420
Article no.: 101669

PACKAGING INFORMATION

State of origin	AT
Customs tariff number	85423190
Net weight [g]	174
Gross weight [g]	221
Gross width [mm]	104
Gross height [mm]	69
Gross length [mm]	120
Net width [mm]	85
Net height [mm]	59
Net length [mm]	105

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at