BLHDS 600

BLHDS0600024DC06520930000W05

Article no.: 171004

BETTER LIGHT





24	20	350	560
Lamp voltage	Length of particular segments	Number of lamps per meter	Luminous flux per meter

TENDER TEXT

BILTON High Density Standard 600 LED strip 24VDC 6,5W/m IP20 CRI>90 3000K WHITE 5m LED module BLHDS 600 Article 171004 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BLHDS 600 LED-strip has a luminous flux of 560 at 6.5 , resulting in an efficiency of 86 . At a nominal voltage of 24 DC on the connection, a maximum module length of 4000 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 20 , resulting in a LED distance of 2.86 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 x 1.2

TOP-FEATURES

//__ Incredible homogeneity through ###attribute.6040### LEDs per meter

//__ Guaranteed LED properties with guaranteed patent protection

//__ The BLHDS 600 can be separated all 20

24 >90 IP20 3000 RoHS COMPLIANT 2002/95/EC CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BLHDS 600

BLHDS0600024DC06520930000W05
Article no.: 171004

BETTER LIGHT

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94054099
Net weight [g]	49
Gross weight [g]	175
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.2
Net length [mm]	5000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at