

# BLONE 1300 >90

BLO191300024DC12820922000W05

Article no.: 101513



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

BL ONE 1300 LED strip 24VDC 12,8W/m IP20 CRI>90 2200K WHITE 5m LED module  
BLONE 1300 >90 Article 101513 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BLONE 1300 >90 LED-strip has a luminous flux of 1090 at 12.8 , resulting in an efficiency of 85 . At a nominal voltage of 24 DC on the connection, a maximum module length of 8000 can be achieved. In terms of lighting, the module has a colour temperature of 2200 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 x 1.5

## TOP-FEATURES

- //\_\_ Best light quality for shop lighting with CRI >90
- //\_\_ Improvement of homogeneity by 20 additional LEDs per meter
- //\_\_ Wide choice of light colors and lumen packages
- //\_\_ With a maximum module length of up to 8000 long, linear lighting lines can be implemented
- //\_\_ UL certification available



# BLONE 1300 >90

**BLO191300024DC12820922000W05**

Article no.: 101513



## PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054099
Net weight [g]	49
Gross weight [g]	175
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)