
BLO19 3000 >90

BLO193000024DC317X6930000W05

Article no.: 101776

BETTER LIGHT





24	3000	>90	2880
Lamp voltage	Max. length	Colour rendering index CRI	Luminous flux per meter

TENDER TEXT

BILTONONE 3000 LED strip 24VDC 31,7W/m IPX6 CRI>90 3000K WHITE 5m LED module BLO19 3000 >90 Article 101776 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BLO19 3000 >90 LED-strip has a luminous flux of 2880 at 31.7 , resulting in an efficiency of 91 . At a nominal voltage of 24 DC on the connection, a maximum module length of 3000 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IPX6 Dimension (L x W x H): 5000 x 8 x 1.5

TOP-FEATURES

//__ Best light quality for shop lighting with CRI >90

//__ Improvement of homogeneity by 20 additional LEDs per meter

//__ Wide choice of light colors and lumen packages

//__ With a maximum module length of up to 3000 long, linear lighting lines can be implemented

24 >90 IPX6 3000 RoHS COMPLIANT 2002/95/EC CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BLO19 3000 >90

BLO193000024DC317X6930000W05
Article no.: 101776

PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054099
Net weight [g]	50.4
Gross weight [g]	179.2
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.