TWO TW Control

BLTWOEMOC24DC00FUNK00120







TENDER TEXT

BILTON TWO EMOTION Control 24VDC RADIO IP20 BILTON TWO TW Control Article 170738 The controller TWO TW Control is operated with Funk and is served with a Funk . The controller and has an output voltage of 24 . The power dissipation in stand-by is . Dimension (L x W x H): $80 \times 40 \times 16$









TWO TW Control

BLTWOEMOC24DC00FUNK00120

Article no.: 170738



MECHANICAL DATA

Material	Kunststoff
Width of device	40
Height of device	16
Depth of device	80
Mounting method	sonstige
Colour	White
Surface protection	sonstige
Control signal	Funk
Material quality	Duroplast
Type of fastening	sonstige
Applicable with movement sensor	yes
Applicable with transmission button	yes
Applicable with infrared button	nein
Applicable with presence indicator	yes
Applicable with time switch/timer	yes
Applicable with button	nein
Surface finishing	matt
Suitable for degree of protection (IP)	IP20

ELECTRICAL DATA

Control signal	Funk
Type of load	sonstige
Serial dimmer	nein
Nominal power	120
Nominal voltage	24

LIGHT TECHNICAL DATA

Light value memory yes

PACKAGING INFORMATION

State of origin	IT
Customs tariff number	85423190
Net width [mm]	40
Net height [mm]	16
Net length [mm]	80

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can



BLTWOEMOC24DC00FUNK00120

Article no.: 170738

