

# BL AIR SIDE 600 EOL

BL AIR Side LED lighth tube 600lm/m 24VDC 13.8W/m IP67 840 1m

Article no.: 102143



24

Lamp voltage

5010

Max. length

>80

Colour rendering index CRI

600

Luminous flux per meter

## TENDER TEXT

AIR SIDE LED lighth tube, LED strip in silicone sheath, 600 lm/m, curved bend to light emission surface, cable connection at one end, cable outlet at rear, OSP Flex, 24VDC 13.8W/m IP67 CRI>80 4000K WHITE 1m LED module BL AIR SIDE 600 EOL Article 102143 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +55 at a service life of 50000 . At an ambient temperature of 85°C, a lifetime of 50,000 hours can still be guaranteed. Up to 95°C the lifetime is 30,000 hours and at temperatures of 100°C still 16,000 hours (> L70B50). The BL AIR SIDE 600 EOL LED-strip has a luminous flux of 600 at 13.8 , resulting in an efficiency of 43 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5010 can be achieved. In terms of lighting, the module has a colour temperature of 4000 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP67 Smallest possible bending radius 200 Dimension (L x W x H): 1010 x 13.2 x 16

## TOP-FEATURES

//\_\_ Homogeneously luminous light line without visible light points

//\_\_ IP67 -protection in highly flexible silicone jacket

//\_\_

UL certified

//\_\_ New connection: the end caps close straight to the profile

# BL AIR SIDE 600 EOL

**BL AIR Side LED lighth tube 600lm/m 24VDC 13.8W/m IP67 840 1m**

Article no.: 102143



# BL AIR SIDE 600 EOL

BL AIR Side LED light tube 600lm/m 24VDC 13.8W/m IP67 840 1m

Article no.: 102143



## MECHANICAL DATA

Width	13.2
Length	1010
Height/depth	16
Height	16
Colour	White
Model	Schlauch
Self-adhesive	nein
Lamp type	LED nicht austauschbar
Distance	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP67
Length of particular segments	50
Lowest bending radius	200
Number of lamps per meter	140

## ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	13.8
Overall efficiency	43

## LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Colour temperature	4000
Colour of light	White
Luminous flux per meter	600
Colour consistency (McAdam ellipse)	SDCM3

## CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	5010

## TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 20 ... + 55
Ambient temperature during operating	- 20 ... + 55

Rated life time L80/B10 at 25 °C

50000

# BL AIR SIDE 600 EOL



## PACKAGING INFORMATION

Article no.: 102143

State of origin

AT

Customs tariff number

94054039

Net weight [g]

0.125

Gross weight [g]

0.125

Gross width [mm]

330

Gross height [mm]

27

Gross length [mm]

330

Net width [mm]

13.2

Net height [mm]

16

Net length [mm]

1010

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)