




BÖ AIR TOP 1300 EOL

BL AIR Top LED lighth tube 1300lm/m 24VDC 15.7W/m IP67 827 1m

Article no.: 102135



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

AIR TOP LED lighth tube, LED strip in silicone sheath, 1300 lm/m, wave-shaped bend to light emission surface, cable connection on one side, cable outlet at bottom, OSP Flex, 24VDC 15.7W/m IP67 CRI>80 2700K WHITE 1.01m LED module BÖ AIR TOP 1300 EOL Article 102135 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +55 at a service life of 50000 . At an ambient temperature of 85°C, a lifetime of 50,000 hours can still be guaranteed. Up to 95°C the lifetime is 30,000 hours and at temperatures of 100°C still 16,000 hours (> L70B50). The BÖ AIR TOP 1300 EOL LED-strip has a luminous flux of 1300 at 15.7 , resulting in an efficiency of 83 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5010 can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP67 Smallest possible bending radius 200 Dimension (L x W x H): 1010 x 13.2 x 12

TOP-FEATURES

- //__ Homogeneously luminous light line without visible light points
- //__ IP67 -protection in highly flexible silicone jacket
- //__
- UL certified
- //__ New connection: the end caps close straight to the profile

BL AIR TOP 1300 EOL

BL AIR Top LED light tube 1300lm/m 24VDC 15.7W/m IP67 827 1m

Article no.: 102135



MECHANICAL DATA

Width	13.2
Length	1010
Height/depth	12
Height	12
Colour	White
Model	Schlauch
Self-adhesive	nein
Lamp type	LED nicht austauschbar
Distance	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP67
Length of particular segments	50
Lowest bending radius	200
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	15.7
Overall efficiency	83

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Colour temperature [K]	2700
Colour of light	White
Luminous flux per meter	1300
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	5010

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature - 20 ... + 55
BL AIR Top LED light tube 1300lm/m 24VDC 15.7W/m IP67 827 1m
Ambient temperature during operating - 20 ... + 55
Article no.: 102135
Rated life time L80/B10 at 25 °C 50000



PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054039
Net weight [g]	0.125
Gross weight [g]	0.125
Gross width [mm]	330
Gross height [mm]	27
Gross length [mm]	330
Net width [mm]	13.2
Net height [mm]	12
Net length [mm]	1010

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at