


BL AIR TOP TW

BL AIR Top LED tube 700lm/m 24VDC 9.9W/m IP67 825-848 5m Colour Change

Article no.: 102146



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

AIR TOP LED light tube, LED strip in silicone sheath, 700 lm/m, wave-shaped bend to light emission surface, cable connection on one side, straight cable outlet, 24VDC 9.9W/m IP67 CRI>80 2500-4800K Colour Change White 5m LED module BL AIR TOP TW Article 102146 The BL AIR TOP TW LED light tube has a luminous flux of 700 at a power of 9.9, which results in an efficiency of 71. With a nominal voltage of 24 DC at the connection, a maximum module length of 5045 can be achieved. In terms of lighting, the module has a color temperature of 2500-4800 and a beam angle of 120. All with a color rendering index of >80 and a binning selection according to SDCM3 (MacAdams). The light strip can be divided every 50, resulting in an LED spacing of 10.71. Protection class IP67, Smallest possible bending radius 200. At an ambient temperature of 85°C, a service life of 50,000 hours can still be guaranteed. Up to 95°C, the service life is 30,000 hours and at temperatures of 100°C it is still 16,000 hours (L70B50). Dimensions (L x W x H): 5045 x 13.2 x 12

TOP-FEATURES

- //_ Homogeneously luminous light line without visible light points
- //_ IP67 -protection in highly flexible silicone jacket
- //_ New connection: the end caps close straight to the profile



BL AIR TOP TW

BL AIR Top LED tube 700lm/m 24VDC 9.9W/m IP67 825-848 5m Colour Change

Article no.: 102146



PACKAGING INFORMATION

| | |
|-----------------------|----------|
| State of origin | AT |
| Customs tariff number | 94054039 |
| Net weight [g] | 609 |
| Gross weight [g] | 609 |
| Gross width [mm] | 330 |
| Gross height [mm] | 27 |
| Gross length [mm] | 330 |
| Net width [mm] | 13.2 |
| Net height [mm] | 12 |
| Net length [mm] | 5045 |

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

| Article | Article no. |
|--|-------------|
| Mounting clip for AIR TOP | 171149 |
| Safety clip for AIR TOP | 170918 |
| Surface mounted profile PC for AIR TOP | 170885 |

End cap set for AIR TOP
BL AIR TOP TW

171555

BL AIR Top LED tube 700lm/m 24VDC 9.9W/m IP67 825-848 5m Colour Change
Article no.: 102146



Surface mounted profile Alu for
AIR TOP

171031

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at