
BL AIR24 Vibe Top 10W

BL AIR24 Vibe Top LED light tube 680lm/m 24VDC 10W/m IP67 927 50m

Article no.: 172294





WAGO Winsta© ready



24	10000	>90	680
Lamp voltage	Max. length	Colour rendering index CRI	Luminous flux per meter

TENDER TEXT

LED light tube AIR24 Vibe Top 680lm/m, silicone, 24 VDC, 10W/m, 68 lm/W, IP67 (without dark areas), CRI >90, 2700 K, one-sided cable 50 cm, cabel exit bottom, 50 meters LED module BL AIR24 Vibe Top 10W Article 172294 The BL AIR24 Vibe Top 10W is a linear LED light strip in a highly flexible silicone sheath. The LED module can be bent in a wave shape in the direction of the light exit surface. It is resistant to salt solution, acid and alkali corrosion. It is flame-retardant and UV-resistant. Suitable for ambient temperatures of -40 ... +60 with a service life of 84000 . The BL AIR24 Vibe Top 10W LED light strip has a luminous flux of 680 at an output of 10 , which results in an efficiency of 68 . With a nominal voltage of 24 DC at the connection, a maximum module length of 10000 can be achieved. In terms of lighting, the module has a color temperature of 2700 and a beam angle of 114 . All with a color rendering index of >90 . The light strip can be divided every 50 , which results in an LED spacing of 3.125 . Protection class IP67 , Smallest possible bending radius 60 Dimensions (L x W x H): 50000 x 13 x 12

TOP-FEATURES

//__ Salt solution resistance, acid and alkali corrosion resistance, flame retardant resistance, UV resistance

//__ No dark spots

//__ Protection class IP67

//__ Product application: Sign lighting, decorative outdoor/indoor lighting, architectural contour application

24 | >90 | IP67 | 2700

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BL AIR24 Vibe Top 10W

BL AIR24 Vibe Top LED light tube 680lm/m 24VDC 10W/m IP67 927 50m
Article no.: 172294

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	9405423190
Net width [mm]	13
Net height [mm]	12
Net length [mm]	50000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
BL end cap set white for NEON Top	171868
BL mounting set silver for Neon Top 25mm	171866
BL built-up profile for NEON TOP	171286
BL mounting set silver for Neon Top 25mm	171866

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BL AIR24 Vibe Top 10W

BL AIR24 Vibe Top LED light tube 680lm/m 24VDC 10W/m IP67 927 50m
Article no.: 172294

BL end cap set white for NEON Top	171868
BL built-up profile for NEON TOP	171286

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at