
BL AIR24 Vibe Top 15W

BL AIR24 Vibe Top LED light tube 980lm/m 24VDC 15W/m IP67 940 50m
Article no.: 172299





24	5000	>90	980
Lamp voltage	Max. length	Colour rendering index CRI	Luminous flux per meter

TENDER TEXT

LED light tube AIR24 Vibe Top 980lm/m, silicone, 24 VDC, 15W/m, 65 lm/W, IP67 (without dark areas), CRI >90, 4000 K, one-sided cable 50 cm, cabel exit bottom, 50 meters LED module BL AIR24 Vibe Top 15W Article 172299 The BL AIR24 Vibe Top 15W is a linear LED light strip in a highly flexible silicone sheath. The LED module can be bent in a wave shape in the direction of the light exit surface. It is resistant to salt solution, acid and alkali corrosion. It is flame-retardant and UV-resistant. Suitable for ambient temperatures of -40 ... +60 with a service life of 84000 . The BL AIR24 Vibe Top 15W LED light strip has a luminous flux of 980 at an output of 15 , which results in an efficiency of 65 . With a nominal voltage of 24 DC at the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a color temperature of 4000 and a beam angle of 114 . All with a color rendering index of >90 . The light strip can be divided every 50 , which results in an LED spacing of 3.125 . Protection class IP67 , Smallest possible bending radius 60 Dimensions (L x W x H): 50000 x 13 x 12

TOP-FEATURES

//__ Salt solution resistance, acid and alkali corrosion resistance, flame retardant resistance, UV resistance

//__ No dark spots

//__ Protection class IP67

//__ Product application: Sign lighting, decorative outdoor/indoor lighting, architectural contour application

24 >90 IP67 4000

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BL AIR24 Vibe Top 15W

BL AIR24 Vibe Top LED light tube 980lm/m 24VDC 15W/m IP67 940 50m
Article no.: 172299

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	9405423190
Net width [mm]	13
Net height [mm]	12
Net length [mm]	50000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
BL mounting set silver for Neon Top 25mm	171866
BL end cap set white for NEON Top	171868
BL built-up profile for NEON TOP	171286
BL mounting set silver for Neon Top 25mm	171866

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BL AIR24 Vibe Top 15W

BL AIR24 Vibe Top LED light tube 980lm/m 24VDC 15W/m IP67 940 50m
Article no.: 172299

BL end cap set white for NEON Top	171868
BL built-up profile for NEON TOP	171286

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at