

BL Casambi Broadcast active

BL Casambi Broadcast control module, universal, active

Article no.: 171450



TENDER TEXT

LED control, input voltage 230VAC. Maximum total output 100W at 230VAC (max. 0.6A). SSR in the phase. Mains output 230VAC. 0-10V output: 0-10VDC or standalone DALI. Protection class IP20. Installation protection class II. Dimensions LxWxH = 56.5x35.8x22.3mm BILTON LEDON Technology BL Casambi Broadcast active Article 171450 The controller BL Casambi Broadcast active is operated with Casambi . The controller and has an output voltage of 220-240 . Dimension (L x W x H): 22.3 x 56.5 x 35.8



MECHANICAL DATA

Width of device	56.5
Height of device	35.8
Depth of device	22.3
Control signal	Casambi
Suitable for degree of protection (IP)	IP20

ELECTRICAL DATA

Control signal	Casambi
Nominal power	100
Nominal voltage	220 - 240
Control voltage	230

PACKAGING INFORMATION

State of origin	EE
Net weight [g]	95.6
Gross weight [g]	95.6
Net width [mm]	56.5

Net height [mm]
Net length [mm]

22,3
35,8

BL Casambi Broadcast active



BL Casambi Broadcast control module, universal, active

Article no.: 171450
SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at