

# BL Casambi Broadcast passive

## BL Casambi Broadcast control module universal passive

Article no.: 171941



---

## TENDER TEXT

Control without integrated power supply, DALI, Casambi, IP20 white BILTON LEDON Technology BL Casambi Broadcast passive Article 171941 The controller BL Casambi Broadcast passive is operated with DALI . The controller and has an output voltage of 9,5 - 22,5 . Dimension (L x W x H): 36,6 x 40,4 x 14

---



# BL Casambi Broadcast passive

## BL Casambi Broadcast control module universal passive

Article no.: 171941



## MECHANICAL DATA

Material	Kunststoff
Width of device	40.4
Height of device	14
Depth of device	36.6
Colour	White
Control signal	DALI
Type of fastening	sonstige
Core cross section	0,5 - 1,5
Suitable for degree of protection (IP)	IP20
App controll via Bluetooth	yes

## ELECTRICAL DATA

Voltage type	DC
Number of channels	4
Control signal	DALI
Nominal voltage	9,5 - 22,5
Standby power consumption (solstandby)	0.1

## CONNECTION

Connection type	Steckklemme
Number of channels	4
Core cross section	0,5 - 1,5

## TEMPERATURE TECHNICAL DATA

Ambient temperature during operating	- 20... + 55
--------------------------------------	--------------

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)