
COR Lite 440lm/m

BL COR Lite LED strip 440lm/m 24VDC 4.4W/m IP20 830 5m
Article no.: 171987





24	5000	>80	440
Lamp voltage	Max. length	Colour rendering index CRI	Luminous flux per meter

TENDER TEXT

LED strip light COR Lite 440 lm/m 24VDC 4.4W/m 100 lm/W IP20 CRI>80 3000K WHITE
1m connection cable on both sides including Dupont connector, 5 meters per box

TOP-FEATURES

//__ Excellent value for money

//__ Ideal for indirect lighting

24 | >80 | IP20 | 3000

PACKAGING INFORMATION

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

COR Lite 440lm/m

BL COR Lite LED strip 440lm/m 24VDC 4.4W/m IP20 830 5m

Article no.: 171987

State of origin	CN
Customs tariff number	9405423990
Net weight [g]	92
Gross weight [g]	92
Gross width [mm]	158
Gross height [mm]	13.5
Gross length [mm]	189
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at