

BL COR NNR25

BL COR NNR 25mm light tube 360° 950lm 24VDC 14.4W/m IP65 930 5m


Article no.: 171224



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED light tube NNR, LED strip in round silicone sheath, 950 lm/m, 360° illumination, cable connection on one side with cable length 200 cm, 24VDC, 14.4W/m, IP65, CRI >90, 3000K, diameter 25mm, 5 metres LED module BL COR NNR25 Article 171224 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Suitable for ambient temperatures from -20 ... +55 at a service life of 36000 . The BL COR NNR25 LED-strip has a luminous flux of 950 at 14.4 , resulting in an efficiency of 66 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 360 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 1 . Degree of protection IP65 Dimension (L x W x H): 5000 x 25 x 25

TOP-FEATURES

- //_ Homogeneously illuminated light line with no visible light points
- //_ IP65 protection in highly flexible silicone jacket
- //_ Unlimited freedom of design (flexibly deformable and separable)



BL COR NNR25

BL COR NNR 25mm light tube 360° 950lm 24VDC 14.4W/m IP65 930 5m

Article no.: 171224



PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94054231
Net weight [g]	3000
Gross weight [g]	3360
Gross width [mm]	400
Gross height [mm]	60
Gross length [mm]	400
Net width [mm]	25
Net height [mm]	25
Net length [mm]	5000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 10% (or +/- 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article

Article no.

171232

171233

171229

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be

found at: www.better-light.at

BL COR NNR25

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

BL COR NNR 25mm light tube 360° 950lm 24VDC 14.4W/m IP65 930 5m

Article no.: 171224

