
BL COR Pure COB

BL COR Pure COB LED strip 900lm/m 24VDC 10W/m IP20 930 5m















TENDER TEXT

LED strip light LED type: COB 900 lm/m 24VDC 10W/m 90lm/W IP20 CRI>90 3000K, one-sided connection cable 50 cm, WHITE Colors and BLT label 5 meters

TOP-FEATURES

//_ Dot-free gelb LED light line with large beam angle $142\,$

//__ Color rendering >90

//__ Easy installation













BL COR Pure COB

BL COR Pure COB LED strip 900lm/m 24VDC 10W/m IP20 930 5m

Article no.: 171845



MECHANICAL DATA

| Width | 8 |
|--------------------------------------|-----------------------------|
| Length | 5000 |
| Height/depth | 1.6 |
| Height | 1.6 |
| Colour | gelb |
| Model | Band |
| | |
| Self-adhesive | yes |
| Self-adhesive Lamp type | yes LED nicht austauschbar |
| | |
| Lamp type | LED nicht austauschbar |
| Lamp type Degree of protection (IP) | LED nicht austauschbar IP20 |

ELECTRICAL DATA

| Protection class | III |
|----------------------|-----|
| Voltage type | DC |
| Lamp voltage | 24 |
| Lamp power per meter | 10 |
| Overall efficiency | 90 |

LIGHT TECHNICAL DATA

| Beam angle | 142 |
|--|-------|
| Colour rendering index CRI | >90 |
| Colour temperature | 3000 |
| Colour of light | White |
| Luminous flux per meter | 900 |
| Energy efficiency class of teh built-in lamp | G |
| Colour consistency (McAdam ellipse) | SDCM3 |
| | |

CONNECTION

| Number of poles | 2 |
|-----------------|------|
| Max. length | 5000 |

TEMPERATURE TECHNICAL DATA

| Ambient temperature during operating | - 25 + 40 |
|--------------------------------------|-----------|
|--------------------------------------|-----------|

PACKAGING INFORMATION

| State of origin | CN | |
|-----------------|----|--|

| Customs fariff number | 9405423990 | |
|--------------------------------|------------------------------|--------------|
| Net Weight 1817 PUTE CO | JB ₁₂₀ | |
| BIC COR Pure COB LED strip 900 | lm/m 24VDC 10₩/m IP20 930 5m | |
| Netwieth 6:1171845 | 8 | |
| Net height [mm] | 1.6 | BETTER LIGHT |
| Net length [mm] | 5000 | |

^{*} Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at $25\,^{\circ}$ C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15% at ECO / TWO / RGB / AIR). Module length at $24\ V$ input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at