


# COR Pure Tone

BL COR Pure Tone LED strip 700lm/m 24VDC 19.2W/m IP20 RGB+830 5m

Article no.: 171853




Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

LED strip RGBW 700 lm/m 24VDC, 19.2W/m, IP20, RGB+3000K, Colors and BLT label, one-sided connection cable 50 cm, 5 meters LED module COR Pure Tone Article 171853 Linear RGBW LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +40 at a service life of 60000 . The COR Pure Tone LED-strip has a luminous flux of 700 at 19.2 , resulting in an efficiency of 36 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a colour temperature of RGB+3000 and a beam angle of 125 . White light component with a colour rendering index of >80 . The light strip can be separated every 100 , resulting in a LED distance of 16.67 . Degree of protection IP20 Dimension (L x W x H): 5000 x 12 x 2.1

## TOP-FEATURES

- //\_\_ RGB+3000 LED strip
- //\_\_ High quality FPC
- //\_\_ Self-adhesive with 3M adhesive tape



# COR Pure Tone

**BL COR Pure Tone LED strip 700lm/m 24VDC 19.2W/m IP20 RGB+830 5m**

Article no.: 171853



## PACKAGING INFORMATION

State of origin	CN
Customs tariff number	9405423990
Net weight [g]	147
Gross weight [g]	147
Net width [mm]	12
Net height [mm]	2.1
Net length [mm]	5000

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR ). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)