

BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted lumi. 300mm 1900lm 18W 120D 830/40/57 WH IP54 MS

Article no.: 732001



yes

With movement sensor

IK08

Impact strength

IP54

Degree of protection (IP)

18

Max. system power

TENDER TEXT

LED wall and ceiling light, 1,900 lumen, 18W, 120° direct beam, colour change: CRI >80, 3,000 & 4,000 & 5700 Kelvin, IP54, IK08, protection class III, non-dimmable, UGR BL Ceiling & wall luminaires Pure Article 732001 The perfect solution for lighting hallways and stairwells in private or public areas. The desired light color (3000 & 4000 & 5700) can be set directly on the LED light. Housing Kunststoff White Fastening using Haltebügel auf der Rückseite . With integrated motion detector - yes . Luminous flux 1900 with an efficiency of and a color rendering of >80 , total power 18 , beam angle 120 , service life 50000 , protection class IP54 , UGR

TOP-FEATURES

//__ Quick installation with 3-pole plug-in clip and Haltebügel auf der Rückseite

//__ Homogeneous light distribution over the entire light emission surface



BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted lumi. 300mm 1900lm 18W 120D 830/40/57 WH IP54 MS

Article no.: 732001



MECHANICAL DATA

Material housing	Kunststoff
Colour housing	White
Width	300
Length	300
Height	58
Diameter	300
Outer diameter	300
Mounting method	Aufbau
UV-resistant	yes
With movement sensor	yes
Lamp type	LED nicht austauschbar
Type of fastening	Haltebügel auf der Rückseite
Material of the cover	Plastic opal
Impact strength	IK08
Degree of protection (IP)	IP54
With lamp	yes
Surface finishing	matt
Control gear included	yes
Unified Glare Ratio (UGR)	<25

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Max. inrush current	40
Nominal voltage	220 - 240
Operating frequency	50 / 60
Max. system power	18
Power factor	0.9
No dim function	yes
Flicker percent (< 165 Hz)	<5

LIGHT TECHNICAL DATA

Function	Farbwechsel, Bewegungsmelder
Beam angle	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	1900
Colour temperature	3000 & 4000 & 5700
Colour of light	White

Energy efficiency class of the built-in lamp F

BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted lumi. 300mm 1900lm 18W 120D 830/40/57 WH IP54 MS

Article no.: 732001

Connection type

3 - pole plug - in clip



TEMPERATURE TECHNICAL DATA

Impact strength	IK08
Ambient temperature during operating	- 20 ... + 40
Rated life time L70/B10 at 25 °C	50000

PACKAGING INFORMATION

State of origin	CN
Net weight [g]	760
Gross weight [g]	1130
Net width [mm]	300
Net height [mm]	58
Net length [mm]	300

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at