

Ceiling- & Wall luminiare Trend

BL CWL Trend+ surface/pendant lum. 875mm 9000lm 90W 90D/I 830-840 black DALI















according to IEC 62722-2-1

TENDER TEXT

LED CWL pendant luminaire, 9,000 lumens, 90W, 90° direct/indirect illumination, CRI >80, 3,000 - 4,000 Kelvin, IP20, protection class I, DALI dimmable, UGR Ceiling- & Wall luminiare Trend Article 731025 Modern surface lights with a wide range of possible uses for representative environments. Whether as a wall or ceiling-mounted version with direct/indirect light component. Mounting type . The color temperature 3000-4000 can be selected via dip switch. Housing Aluminium Black , Cover material Plastic structured , Luminous flux 9000 with an efficiency of 100 and a color rendering of >80 , Total power 90 , Beam angle 90 , Service life 50000 , Protection class IP20 , UGR

TOP-FEATURES

//_ Color temperature selectable via dip switch 3000-4000 $\,$

//__ Light emission direct/indirect

//__ Housing Aluminium Black











Ceiling- & Wall luminiare Trend

BL CWL Trend+ surface/pendant lum. 875mm 9000lm 90W 90D/I 830-840 black DALI

Article no.: 731025



MECHANICAL DATA

Material housing	Aluminium
Colour housing	Black
Width	875
Length	875
Height	91
Diameter	875
With movement sensor	nein
Type of control gear	LED - Betriebsgerät stromgesteuert
Lamp type	LED nicht austauschbar
Material of the cover	Plastic structured
Degree of protection (IP)	IP20
Suspension included in delivery	nein
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	I
Voltage type	AC
Nominal voltage	200 - 240
Type of dimming	DALI
Overall efficiency	100
Max. system power	90
Power factor	0.9

LIGHT TECHNICAL DATA

rect
I

TEMPERATURE TECHNICAL DATA

Rated life time L90/B50 at 25 °C 50000

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94051098
Net weight [g]	11010

Gross weight [g] Wall luminiare 12170 rend Bio Wight Field + surface/pendant lum. 875mm 9000 90D/I 830-840 black DALI Article 18th: 17791025 Net width [mm] 875 BETTER LIGHT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

91

875

Net height [mm]

Net length [mm]

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at