
BL Downlight Office

BL Downlight Office recessed luminaire D170mm 1800lm 18W 60D 940 white 450mA

Article no.: 728055














TENDER TEXT

LED recessed downlight round, white aluminium housing, without power supply unit, 1,800 lumen, 18W, 60° direct beam, CRI >90, 4,000 Kelvin, IP44, dimensions: D 170 x H 112 mm BL Downlight Office Article 728055 LED ceiling recessed downlight - control gear - nein , made of high-quality, White coated Aluminium frame; best light quality and homogeneous symmetrical light distribution across the entire light emission surface, protection class IP44 , luminous flux 1800 , connected load 18 , luminous efficacy 100 , color rendering >90 , light color White , color temperature 4000 , beam angle 60 , dimensions: 170 x 112 , ceiling cutout 139

TOP-FEATURES

//_ This high-quality downlight offers a glare limitation of $\!\!<\!19$

//__ Protection class (room side) IP44

//_ COB light source

//__ Plug&Play connection











BL Downlight Office

BL Downlight Office recessed luminaire D170mm 1800lm 18W 60D 940 white 450mA

Article no.: 728055



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width	170
Length	170
Height/depth	112
Diameter	170
Installation diameter	139
Outer diameter	170
Mounting method	Einbau
Lamp type	LED nicht austauschbar
Degree of protection (IP)	IP44
Control gear included	nein
Installation height/depth	112
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage	33 - 38
Overall efficiency	100
Max. system power	18

LIGHT TECHNICAL DATA

Beam angle	60
Colour rendering index CRI	>90
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	1800
Colour temperature	4000
Colour of light	White

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating	- 20 + 45
Rated life time L80/B10 at 25 °C	50000

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94051190
Net weight [g]	500
Gross weight [g]	640

Gross width [mm]	190	
Bross width [mm] Vnlight Off	1CE 140	
Bio Downlight Office recessed lumin	aire D170mm 1800lm 18W 60D 940 white 450m	nA .
Netwieth6::1728055	170	
Net height [mm]	112	BETTER LIGHT
Net length [mm]	170	

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at