
BL Downlight Protected

BL Downlight Protected recessed luminaire 145mm 2000lm 17W 60D 840 WH IP54 450mA

Article no.: 723006









TENDER TEXT

LED recessed downlight round, 2,000 lumen, 17W, 60° direct beam, CRI >80, 4,000 Kelvin, IP54, protection class III, non-dimmable, white aluminium housing, without power supply unit, dimensions: D 145mm x H 78mm, ceiling outlet: D135mm BL Downlight Protected Article 723006 BL Downlight Protected LED downlight with easy installation and commissioning of the LED power supply unit thanks to the pre-installed connection cable; highly efficient reflector made of Aluminium , high-quality, White cooling housing made of aluminum, excellent thermal management, protection class IP54 on the room side; shock resistance ; protection class III , luminaire luminous flux 2000 ; Connected load 17 W, color rendering >80 , light color White , color temperature 4000 , beam angle 60 , glare-free light distribution using a special reflector, UGR

TOP-FEATURES

 $//_$ Excellent glare value of UGR <19

//__ Aluminum reflector with mirror optics§

//__ Protection class (room side) IP54

//__ Plug&Play Connection











BL Downlight Protected

BL Downlight Protected recessed luminaire 145mm 2000lm 17W 60D 840 WH IP54 450mA

Article no.: 723006



MECHANICAL DATA

Colour housingWhiteWidth145Length145Height/depth78Diameter145Installation diameter135
Length145Height/depth78Diameter145
Height/depth 78 Diameter 145
Diameter 145
Installation diameter 135
Outer diameter 145
Mounting method Einbau
With movement sensor nein
With light sensor nein
Lamp type LED nicht austauschbar
Degree of protection (IP) IP54
With lamp yes
Control gear included nein
Unified Glare Ratio (UGR) <19

ELECTRICAL DATA

Protection class	III
Amperage	0.45
Max. system power	17

LIGHT TECHNICAL DATA

Beam angle	60
Colour rendering index CRI	>80
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	2000
Colour temperature	4000
Colour of light	White
Flicker-free	yes

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94051190
Net weight [g]	475
Gross weight [g]	575

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our

knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at 100 WHO INSTITUTE OF THE COLOR O

BL Downlight Protected recessed luminaire 145mm 2000lm 17W 60D 840 WH IP54 450mA

Article no.: 723006



BETTER LIGHT