


BL Downlight Pure Mounted R

BL Downlight Pure surface-mounted 225mm 2000lm 21W 110D 840 WH IP44 700mA

Article no.: 722019



Mounting method



Degree of protection (IP)



Diameter



Flicker-free

TENDER TEXT

LED surface-mounted downlight round, 2,000 lumens, 21W, 110° direct beam, CRI >80, 4,000 Kelvin, IP44, IK05, protection class III, dimmable, UV-resistant, EEC F, white aluminium housing, without power supply unit, dimensions: D 225mm x H 35mm BL Downlight Pure Mounted R Article 722019 LED Aufbau downlight with power supply yes ; including fastening material; compact design with high-quality, White coated Aluminium frame; best light quality and homogeneous, symmetrical light distribution across the entire light emission surface; UV-resistant yes , Protection class IP44 , Shock resistance IK05 , Luminous flux 2000 , Connected load 21 , Luminaire luminous efficacy 95 , Color rendering >80 , Light color White , Color temperature 4000 K, Beam angle 110 , Ambient temperature -20 ... +40 , Dimensions: 225 x 225 x 35

TOP-FEATURES

- //__ Round and square design
- //__ Installation height 35
- //__ Protection class IP44
- //__ Plug&Play Connection



BL Downlight Pure Mounted R

BL Downlight Pure surface-mounted 225mm 2000lm 21W 110D 840 WH IP44 700mA

Article no.: 722019



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width	225
Length	225
Height/depth	35
Diameter	225
Mounting method	Aufbau
UV-resistant	yes
Impact strength	IK05
Degree of protection (IP)	IP44
With lamp	yes
Control gear included	yes

ELECTRICAL DATA

Protection class	III
Amperage	0.7
Voltage type	DC
Nominal voltage	27 - 30
Overall efficiency	95
Max. system power	21
Dimming depending on control gear	yes

LIGHT TECHNICAL DATA

Beam angle	110
Colour rendering index CRI	>80
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	2000
Colour temperature [K]	4000
Colour of light	White
Energy efficiency class of the built-in lamp	F
Colour consistency (McAdam ellipse)	SDCM4
Flicker-free	yes

TEMPERATURE TECHNICAL DATA

Impact strength	IK05
Ambient temperature during operating	- 20 ... + 40
Rated life time L80/B10 at 25 °C	50000

PACKAGING INFORMATION

State of origin CN
Net weight [g] 340

BL Downlight Pure Mounted R

Gross weight [g] 625
BL Downlight Pure surface-mounted 225mm 2000lm 21W 110D 840 WH IP44 700mA

Net width [mm] 225
Article no.: 722019

Net height [mm] 35

Net length [mm] 225



BETTER LIGHT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at