



BL Downlight UGR Flat

BL Downlight UGR Flat recessed luminaire 380mm 1700lm 15W 90D 840 white 450 mA

Article no.: 723020



Height/depth



Colour housing



Degree of protection (IP)



Rated luminous flux
according to IEC
62722-2-1

TENDER TEXT

Extra flat round downlight with UGR80, 4000K, D380 x T10.5mm, with 3 spring clamps BL Downlight UGR Flat Article 723020 LED ceiling recessed downlight - operating device nein made of high-quality, White coated Aluminium frame; best light quality and homogeneous symmetrical light distribution across the entire light emission surface, protection class IP20 ; Shock resistance , Luminous flux 1700 , Connected load 15 , Luminaire luminous efficacy 113 , Color rendering >80 , Light color White , Color temperature 4000 K, Beam angle 90 , Dimensions: 380 x 10.5 , Ceiling cutout 365

TOP-FEATURES

- //_ Use where space is limited in the ceiling
- //_ Glare limitation <19 despite low height of 10.5
- //_ Plug&Play connection



BL Downlight UGR Flat

BL Downlight UGR Flat recessed luminaire 380mm 1700lm 15W 90D 840 white 450 mA

Article no.: 723020



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width	380
Length	380
Height/depth	10.5
Installation diameter	365
Outer diameter	380
Mounting method	Einbau mit 3 Federklemmen
Reflector	White
With movement sensor	nein
Lamp type	LED austauschbar
Degree of protection (IP)	IP20
With lamp	yes
Control gear included	nein
Suitable for ceiling mounting	yes
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Voltage type	AC
Nominal voltage	230
Overall efficiency	113
Max. system power	15

LIGHT TECHNICAL DATA

Beam angle	90
Colour rendering index CRI	>80
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	1700
Colour temperature [K]	4000
Colour of light	White

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C	50000
----------------------------------	-------

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94054239
Net weight [g]	1180
Gross weight [g]	1370

Net width [mm] 380
Net height [mm] 380

Net length [mm] 105
BL Downlight UGR Flat recessed luminaire 380mm 1700lm 15W 90D 840 white 450 mA

Article no.: 723020

NECESSARY ACCESSORIES



Article

Article no.

**LED DRIVER 220-240V CC
450mA 27-45VDC ON/OFF**

729160

**LED DRIVER 220-240V CC
450mA 9-45VDC DALI**

729157

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at