

# BL Drive IP20 100W Slim

BL ECO power supply unit CV 220-240VAC 100W 24VDC 4200mA IP20

Article no.: 170166



Output voltage range



Output power range



Degree of protection (IP)

---

## TENDER TEXT

Constant voltage power supply unit. Input voltage 220-240VAC. Maximum total power 100W (max. 4.2A). Output voltage 24VDC. Protection class IP20. Protection class II. Dimensions LxWxH = 305x30x24mm BILTON LEDON TechnologyBL Drive IP20 100W Slim Article 170166 The power supply can be used up to 100 output power and 24 output voltage. The supply voltage of the power supply is 220 - 240 and has a IP20 protection class and protection class II . Dimension (L x W x H): 305 x 30 x 24



# BL Drive IP20 100W Slim

**BL ECO power supply unit CV 220-240VAC 100W 24VDC 4200mA IP20**

Article no.: 170166



## PACKAGING INFORMATION

State of origin	DE
Customs tariff number	85043180
Net weight [g]	185
Gross weight [g]	208
Gross width [mm]	33
Gross height [mm]	27
Gross length [mm]	308
Net width [mm]	30
Net height [mm]	24
Net length [mm]	305

## NECESSARY ACCESSORIES

Article

Article no.

**BL Endcap set for BL Dirve Slim**

**170548**

**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)

# BL Drive IP20 100W Slim

## BILTON ECO POWER SUPPLY

BL ECO power supply unit CV220-240V AC 100W 24V DC 4.200mA IP20

Article no.: 170166

Possible power supply units per  
safety automatic machine

ART. NO.	TYPE	PEAK CURRENT	TIME	CHARACTER B				CHARACTER C			
				6 A	10 A	13 A	16 A	6 A	10 A	13 A	16 A
		[A]	[ $\mu$ s]	6 A	10 A	13 A	16 A	6 A	10 A	13 A	16 A
170160	ECO 40	21	275	8	13	17	21	13	22	29	35
170162	ECO 60	24	275	7	11	15	18	11	19	25	31
170166	ECO 100	34	385	3	5	7	9	5	9	12	15