BL High Bays Pure


BL HB Pure+ pendant luminaire 258mm 15000lm 100W 120D 840 230V

Article no.: 742088















Degree of protection (IP)



Control gear included



Rated luminous flux according to IEC 62722-2-1

TENDER TEXT

High bay luminaire made of black aluminium, incl. converter and ring bolt, 15000lm, 100W, 4000K, CRI80, 120°, IP65, IK08 Dimensions: D258x139mm BL High Bays Pure Article 742088 LED High Bay with integrated LED power supply - yes; Mounting type: Suspension using Seilabhängung / Montagebügel, highly efficient lens optics, cooling housing Aluminium Black, excellent thermal management, suitable for ambient temperatures of -40...+60, protection class IP65, shock resistance IK08, service life of 50000, luminous flux 15000, connected load 100, color rendering >80, color temperature 4000, Beam angle 120 , Shock resistance IK08 , Dimensions (D /H): 258 x 139











BL High Bays Pure

BL HB Pure+ pendant luminaire 258mm 15000lm 100W 120D 840 230V

Article no.: 742088



MECHANICAL DATA

Material housing	Aluminium	
Colour housing	Black	
Width	258	
Length	258	
Height/depth	139	
Diameter	258	
Mounting method	Suspension	
Type of control gear	LED - Betriebsgerät stromgesteuert	
Lamp type	LED nicht austauschbar	
Type of fastening	Seilabhängung / Montagebügel	
Impact strength	IK08	
Degree of protection (IP)	IP65	
Control gear included	yes	
Suspension included in delivery	nein	

ELECTRICAL DATA

Protection class	T. Control of the con
Voltage type	AC
Nominal voltage	100 - 277
Operating frequency	50 - 60
Type of dimming	1 - 10 V
Overall efficiency	150
Max. system power	100
Power factor	0.95
Dimming 0-10 V	yes

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	15000
Colour temperature	4000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6

TEMPERATURE TECHNICAL DATA

Impact strength	IK08
Ambient temperature during operating	- 40 + 60



BIANB Pared beardant ruminaire 2580m 15000 m 100W 120D 840 230V

Article no.: 742088 State of origin	CN	BETTER LIGHT
Customs tariff number	94054099	
Net weight [g]	1800	
Gross weight [g]	2400	
Gross width [mm]	305	
Gross height [mm]	145	
Gross length [mm]	305	
Net width [mm]	258	
Net height [mm]	139	
Net length [mm]	258	

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at