BL High Bays Pure


BL HB Pure+ pendant luminaire 299mm 22500lm 150W 120D 850 230V

Article no.: 742092

















62722-2-1

TENDER TEXT

High bay luminaire made of black aluminium, incl. converter and ring bolt, 22500lm, 150W, 5000K, CRI80, 120 $^{\circ}$, IP65, IK08 Dimensions: D299x139mm BL High Bays Pure Article 742092 LED High Bay with integrated LED power supply - yes; Mounting type: Suspension using Seilabhängung / Montagebügel, highly efficient lens optics, cooling housing Aluminium Black, excellent thermal management, suitable for ambient temperatures of -40...+60, protection class IP65, shock resistance IK08, service life of 50000, luminous flux 22500, connected load 150, color rendering >80, color temperature 5000, Beam angle 120, Shock resistance IK08, Dimensions (D /H): 299 x 139











BL High Bays Pure

BL HB Pure+ pendant luminaire 299mm 22500lm 150W 120D 850 230V

Article no.: 742092



MECHANICAL DATA

Material housing	Aluminium	
Colour housing	Black	
Width	299	
Length	299	
Height/depth	139	
Diameter	299	
Mounting method	Suspension	
Type of control gear	LED - Betriebsgerät stromgesteuert	
Lamp type	LED nicht austauschbar	
Type of fastening	Seilabhängung / Montagebügel	
Impact strength	IK08	
Degree of protection (IP)	IP65	
Control gear included	yes	
Suspension included in delivery	nein	

ELECTRICAL DATA

Protection class	T. Control of the con
Voltage type	AC
Nominal voltage	100 - 277
Operating frequency	50 - 60
Type of dimming	1 - 10 V
Overall efficiency	150
Max. system power	150
Power factor	0.95
Dimming 0-10 V	yes

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	22500
Colour temperature	5000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6

TEMPERATURE TECHNICAL DATA

Impact strength	IK08
Ambient temperature during operating	- 40 + 60



BIANB Pared beardaint ruminaine 2799 mm 22500 m 150W 120D 850 230V

Article no.: /42092 State of origin	CN	BETTER LIGHT
Customs tariff number	94054099	
Net weight [g]	2240	
Gross weight [g]	2850	
Gross width [mm]	365	
Gross height [mm]	150	
Gross length [mm]	365	
Net width [mm]	299	
Net height [mm]	139	
Net length [mm]	299	

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at