
## BL High Bays Pure


BL HB Pure+ pendant luminaire 347mm 30000lm 200W 120D 850 230V

Article no.: 742093

















Impact strength

Degree of protection (IP)

Rated luminous flux according to IEC 62722-2-1

#### **TENDER TEXT**

High bay luminaire made of black aluminium, incl. converter and ring bolt, 30000lm, 200W, 5000K, CRI80, 120°, IP65, IK08 Dimensions: D347x142mm BL High Bays Pure Article 742093 LED High Bay with integrated LED power supply - yes; Mounting type: Suspension using Seilabhängung / Montagebügel, highly efficient lens optics, cooling housing Aluminium Black, excellent thermal management, suitable for ambient temperatures of -40...+60, protection class IP65, shock resistance IK08, service life of 50000, luminous flux 30000, connected load 200, color rendering >80, color temperature 5000, Beam angle 120 , Shock resistance IK08 , Dimensions (D /H):  $347 \times 142$ 











# BL High Bays Pure

#### BL HB Pure+ pendant luminaire 347mm 30000lm 200W 120D 850 230V

Article no.: 742093



#### MECHANICAL DATA

Material housing	Aluminium
Colour housing	Black
Width	347
Length	347
Height/depth	142
Diameter	347
Mounting method	Suspension
Type of control gear	LED - Betriebsgerät stromgesteuert
Lamp type	LED nicht austauschbar
Type of fastening	Seilabhängung / Montagebügel
Impact strength	IK08
Degree of protection (IP)	IP65
Control gear included	yes
Suspension included in delivery	nein

## **ELECTRICAL DATA**

Protection class	I
Voltage type	AC
Nominal voltage	100 - 277
Operating frequency	50 - 60
Type of dimming	1 - 10 V
Overall efficiency	150
Max. system power	200
Power factor	0.95
Dimming 0-10 V	yes

## LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	30000
Colour temperature	5000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6

## TEMPERATURE TECHNICAL DATA

Impact strength	IK08
Ambient temperature during operating	- 40 + 60



#### BLATB Pared Dead and Transital Statement 30000 Im 200W 120D 850 230V

Article no.: 742093 State of origin	CN	BETTER LIGHT
Customs tariff number	94054099	
Net weight [g]	3300	
Gross weight [g]	4000	
Gross width [mm]	415	
Gross height [mm]	155	
Gross length [mm]	415	
Net width [mm]	347	
Net height [mm]	142	
Net length [mm]	347	

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at