# BL HVS light tube double-sided on a reel

**BL High Voltage LED ligth tube 940lm/m 230VAC 10W/m IP65 860 25m on reel**

Article no.: 171739



**75000**

Max. length

**IP65**

Degree of protection (IP)

**6000**

Colour temperature

## TENDER TEXT

LED ligth tube High Voltage 940 lm/m two-sided lighting, 230VAC, 10W/m, 94 lm/W, IP65, CRI>80, 6000K, on a reel, 25 meter LED module BL HVS light tube double-sided on a reel Article 171739 LED light tube with lighting on both sides on a practical spool for easy and quick unwinding. Using T-connectors, several light strips can be connected over a total length of 75000 , Supply voltage 230 ; lamp power 10 , luminous flux 940 , IP65 Protection type, color temperature 6000 , Beam angle 120 , Dimensions light tube 13 x height 7 , on a spool, LEDs per meter 288 single row, LED spacing 6.94 , Shock resistance IK07

## TOP-FEATURES

//__ Space-saving and efficiently stackable

//__ UV-resistant, flame retardant class V1-V0

//__ No external power supply required, connect directly to 230 AC

//__ Daylight , homogeneous illumination over the entire length and on both sides of the LED light strip

//__ Using T-connectors, a length of up to 100 meters is possible

230 >80 IP65 6000

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

# BL HVS light tube double-sided on a reel

**BL High Voltage LED ligth tube 940lm/m 230VAC 10W/m IP65 860 25m on reel**
Article no.: 171739

## PACKAGING INFORMATION

| | |
|---|---|
| State of origin | CN |
| Customs tariff number | 94059900 |
| Net weight [g] | 3000 |
| Gross weight [g] | 4500 |
| Gross width [mm] | 250 |
| Gross height [mm] | 250 |
| Gross length [mm] | 135 |
| Net width [mm] | 13 |
| Net height [mm] | 7 |
| Net length [mm] | 25000 |

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR ). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

## NECESSARY ACCESSORIES

| Article | Article no. |
|---|---|
| Cable 800W for LED Light tube | 171742 |
| Cable 1500W for LED Light tube | 171743 |

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at