

BL iTouch Platine

BL iTouch circuit board for 24V light strips with touch function

Article no.: 171735



TENDER TEXT

BL Touch Sensor board for switching on, off and dimming by touch, Double-sided flexible circuit board, DC5~24V / 5A Input voltage = output voltage, 5% ~ 100% brightness dimmable, suitable for flexible LED strips

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	8536500090
Net weight [g]	0.6

Gross weight [g]	7.8
Gross width [mm]	60
Gross height [mm]	60
Gross length [mm]	40
Article No.:	171735
Net width [mm]	8
Net height [mm]	12.5
Net length [mm]	40



* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at