



Linear Trend pendant luminaire

BL Linear Trend pendant luminaire 1167mm 5000lm 45W 90D/I 840 white DALI

Article no.: 701008



Length



Material



Colour temperature



Flicker-free

TENDER TEXT

Linear pendant luminaire, white aluminium housing, reflector optics incl. DALI power supply unit and end caps, 5,000 lumens, 45W, direct and indirect light distribution, CRI >80, 4,000 Kelvin, IP20, dimensions: L 1,167 x W 46 x H 61mm Linear Trend pendant luminaire Article 701008 Linear LED luminaire with combined Linsen- Reflektoroptik optics and direct/indirect lighting; High-quality, White coated profile made of Aluminium , without visible screws, ambient temperatures of -20 ... +40 with a service life of , luminous flux 5000 , connected load 45 , luminous efficacy 111 , colour rendering >80 , UGR

TOP-FEATURES

- //__ Best light quality with precise glare control and homogeneous light distribution
- //__ Available as surface-mounted or pendant light
- //__ Light emission direct/indirect
- //__ Optics Linsen- Reflektoroptik



Linear Trend pendant luminaire

BL Linear Trend pendant luminaire 1167mm 5000lm 45W 90D/I 840 white DALI

Article no.: 701008



MECHANICAL DATA

Material	Aluminium
Colour housing	White
Width [mm]	46
Length	1167
Height/depth	61
Mounting method	Suspension
Lamp type	LED austauschbar
Type of fastening	Seilabhängung
Suitable for strip light configuration	yes
Material of the cover	Linsen - Reflektoroptik
Degree of protection (IP)	IP20
With lamp	yes
Control gear included	yes
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Power factor	0,95
Nominal voltage	220 - 240
Operating frequency	50 / 60
Overall efficiency	111
Max. system power	45
Power factor	0.95
Dimming DALI	yes
Flicker percent (< 165 Hz)	<3

LIGHT TECHNICAL DATA

Beam angle	90
Colour rendering index CRI	>80
Light exit	direct / indirect
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	5000
Colour temperature	4000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Flicker-free	yes

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating

Linear Trend pendant luminaire

- 20 ... + 40

PACKAGING INFORMATION

Linear Trend pendant Luminaire 1167mm 5000lm 45W 90D/I 840 white DALI

Article no.: 701008

State of origin

CN

Net weight [g]

2000

Gross weight [g]

2170

Net width [mm]

46

Net height [mm]

61

Net length [mm]

1167



SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at