



# Linear Trend surface-mounted luminaire

BL Linear Trend surface-mounted luminaire 1167mm 5000lm 45W 110D 840 black DALI

Article no.: 701023



1167

Length



Aluminium

Material



4000

Colour temperature



Yes

Flicker-free

## TENDER TEXT

Linear surface-mounted luminaire, black aluminium housing, opal cover incl. DALI power supply unit, mounting clips and end caps, 5,000 lumens, 45W, 110° direct beam, CRI >80, 4,000 Kelvin, IP20, dimensions: L 1,167 x W 46 x H 61mm Linear Trend surface-mounted luminaire Article 701023 Linear LED luminaire with combined Plastic Opal optics and direkt lighting; High-quality, black coated profile made of Aluminium, without visible screws, ambient temperatures of -20 ... +40 with a service life of 50000, luminous flux 5000, connected load 45, luminous efficacy 111, colour rendering >80, colour consistency SDCM3, UGR

## TOP-FEATURES

//\_\_ Best light quality with precise glare control and homogeneous light distribution

//\_\_ Available as surface-mounted or pendant light

//\_\_ Light emission direkt

//\_\_ Optics Plastic Opal



PACKAGING INFORMATION

# Linear Trend surface-mounted luminaire



State of origin	CN
<b>BL Linear Trend surface-mounted luminaire 1167mm 5000lm 45W 110D 840 black DALI</b>	
Net weight [g]	1720
Article no.: 701023	
Gross weight [g]	1890

**BETTER LIGHT**

Net width [mm]	46
Net height [mm]	61
Net length [mm]	1167

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)