



BL Loop

BL Loop profile luminaire D1500mm 7200lm 80W 110D 840 black DALI


Article no.: 704004



Colour housing



Type of fastening



Rated life time L80/B10 at
25 °C



Dimming DALI

TENDER TEXT

Round LED profile light including suspension, black aluminium housing, 80W, 7.200lm, 4,000K, DALI, CRI>80, 110° direct beam angle, incl. DALI power supply unit, dimensions: 1500 x 60 x 60mm, black Item 704004 LED ring luminaire made of Aluminium Black with power supply - yes, rated voltage AC; cover made of Plastic opal; dimmable DALI yes or ON/OFF; protection class IP20; flicker-free yes; easy to install yes; lifespan of 50000, Luminous flux 7200, Colour temperature 4000, Colour reproduction >80, Beam angle 110, Ambient temperature -20 ... +40 diameter 1500 x height 60 mm

TOP-FEATURES

//__ LED ring light suitable for a wide range of applications for general lighting

//__ Available as switchable on/off or dimmable DALI version

//__ Easy installation



MECHANICAL DATA

Material housing	Aluminium
BL Loop profile luminaire D1500mm 7200lm 80W 110D 840 black DALI	Black
Colour housing	
Article no.: 704004	
Width [mm]	1500
Length [mm]	1500
Height [mm]	60
Diameter	1500
Mounting method	Surface / Suspension
Lamp type	LED austauschbar
Type of fastening	Wire rope
Material of the cover	Plastic opal
Degree of protection (IP)	IP20
With lamp	yes
Control gear included	yes
Suspension included in delivery	yes



ELECTRICAL DATA

Protection class	III
Voltage type	AC
Nominal voltage	220 - 240
Operating frequency	50 / 60
Overall efficiency	90
Max. system power	80
Power factor	0.9
Dimming DALI	yes

LIGHT TECHNICAL DATA

Beam angle	110
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	7200
Colour temperature	4000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6
Flicker-free	yes

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating	- 20 ... + 40
Rated life time L80/B10 at 25 °C	50000

PACKAGING INFORMATION

State of origin	CN
Net width [mm]	1500
Net height [mm]	60

Net length [mm]

1500

BL Loop



SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

BL Loop profile luminaire D1500mm 7200lm 80W 110D 840 black DALI

Article no.: 704004

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

BETTER LIGHT