
BL Loop

BL Loop profile luminaire D1500mm 7200lm 80W 110D 840 black DALI
Article no.: 704004





black	Wire rope	50000	Yes
Colour housing	Type of fastening	Rated life time L80/B10 at 25 °C	Dimming DALI

TENDER TEXT

Round LED profile light including suspension, black aluminium housing, 80W, 7,200lm, 4,000K, DALI, CRI>80, 110° direct beam angle, incl. DALI power supply unit, dimensions: 1500 x 60 x 60mm, black Item 704004 LED ring luminaire made of Aluminium black with power supply - Yes , rated voltage AC ; cover made of Plastic Opal ; dimmable DALI Yes or ON/OFF; protection class IP20 ; flicker-free Yes ; easy to install Yes ; lifespan of 50000 , Luminous flux 7200 , Colour temperature 4000 , Colour reproduction >80 , Beam angle 110 , Ambient temperature -20 ... +40 diameter 1500 x height 60

TOP-FEATURES

//__ LED ring light suitable for a wide range of applications for general lighting

//__ Available as switchable on/off or dimmable DALI version

//__ Easy installation



PACKAGING INFORMATION

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

BL Loop

BL Loop profile luminaire D1500mm 7200lm 80W 110D 840 black DALI
Article no.: 704004

State of origin	CN
Net width [mm]	1500
Net height [mm]	60
Net length [mm]	1500

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at