

LuxAdapt

BL MT Power supply unit CC 220-240VAC 30-46VDC 900mA IP20 LUX ADAPT

Article no.: 719098



ohne

Control signal

IP20

Degree of protection (IP)

TENDER TEXT

Constant current power supply unit with brightness sensor. Input voltage 220-240VAC. Output voltage 30-42VDC. Output current 900mA. Protection class IP20. Protection class II. Dimensions LxWxH = 202x58x30mm

TOP-FEATURES

//__ Plug and play function: simply insert the power supply unit into the BL Comfort Panel – done. Compatible with the BL Comfort Panel series. The power supply unit sets the desired lighting level depending on the existing ambient light.

IP20

PACKAGING INFORMATION

LuxAdapt

State of origin CN
BL MT Power supply unit CC 220-240VAC 30-46VDC 900mA IP20 LUX ADAPT
Customs tariff number 85369095
Article no.: 719098
Net weight [g] 220



BETTER LIGHT

Gross weight [g]	270
Net width [mm]	58
Net height [mm]	30
Net length [mm]	202

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at