


BL NEON Top

BL NEON Top LED light tube 690lm/m 24VDC 10.6W/m IP67 940 5m


Article no.: 171861



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED light tube Neon Top 690lm/m, silicone, 24 VDC, 10.6W/m, 65 lm/W, IP67 (without dark areas), CRI >90, 4000 K, one-sided cable 50 cm, cable exit right, 5 meters LED module BL NEON Top Article 171861 The BL NEON Top is a linear LED light strip in a highly flexible silicone sheath. The LED module can be bent in a wave shape in the direction of the light exit surface. It is resistant to salt solution, acid and alkali corrosion. It is flame-retardant and UV-resistant. Suitable for ambient temperatures of -20 ... +40 with a service life of 60000 . The BL NEON Top LED light strip has a luminous flux of 690 at an output of 10.6 , which results in an efficiency of 65 . With a nominal voltage of 24 DC at the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a color temperature of 4000 and a beam angle of 114 . All with a color rendering index of >90 . The light strip can be divided every 50 , which results in an LED spacing of . Protection class IP67 , Smallest possible bending radius 60 Dimensions (L x W x H): 5000 x 12 x 13

TOP-FEATURES

//_ Salt solution resistance, acid and alkali corrosion resistance, flame retardant resistance, UV resistance

//_ No dark spots

//_ Protection class IP67

//_ Product application: Sign lighting, decorative outdoor/indoor lighting, architectural contour application



BL NEON Top

BL NEON Top LED light tube 690lm/m 24VDC 10.6W/m IP67 940 5m

Article no.: 171861



PACKAGING INFORMATION

State of origin	CN
Customs tariff number	9405423190
Net weight [g]	950
Gross weight [g]	950
Gross width [mm]	410
Gross height [mm]	15
Gross length [mm]	370
Net width [mm]	12
Net height [mm]	13
Net length [mm]	5000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 10% (or +/- 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article

Article no.

**BL mounting set silver for Neon
Top 25mm**

171866

**BL end cap set white for NEON
Top**

171868

**BL built-up profile for NEON
TOP**

171286


SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. We do not accept any liability for errors. Please refer to the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

BL NEON Top

BL NEON Top LED light tube 690lm/m 24VDC 10.6W/m IP67 240.5mm

Article no.: 171861



BETTER LIGHT