


BL ONE Comfort 1300 >80

BL ONE Comfort LED strip 1220lm/m 24VDC 9.1W/m IP20 827 20m
Article no.: 100173



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED strip ONE Comfort 1220 lm/m 24VDC 9.1W/m 134lm/W IP20 CRI>80 2700K, without connection cable, WHITE 20 meter LED module BL ONE Comfort 1300 >80 Article 100173 Linear LED light strip IC-controlled on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 72000 . The BL ONE Comfort 1300 >80 LED-strip has a luminous flux of 1220 at 9.1 , resulting in an efficiency of 134 . At a nominal voltage of 24 DC on the connection, a maximum module length of 7500 can be achieved. In terms of lighting, the module has a colour temperature of 2700 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 . Dimension (L x W x H): 20000 x 8 x 1.5

TOP-FEATURES

- //__ Wide range of lumens and light colours
- //__ Maximum homogeneity thanks to 140 LEDs per metre
- //__ Economical energy consumption
- //__ Produced in Austria



BL ONE Comfort 1300 >80

BL ONE Comfort LED strip 1220lm/m 24VDC 9.1W/m IP20 827 20m

Article no.: 100173



MECHANICAL DATA

Width	8
Length	20000
Height/depth	1.5
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments	50
Lowest bending radius	20
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	9.1
Overall efficiency	134

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Colour temperature	2700
Colour of light	warmweiß
Luminous flux per meter	1220
Energy efficiency class provided exchangeable built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	7500

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	0 ... + 60
Operation temperature at Tc	- 5 ... + 60

Ambient temperature during operating - 20 + 45
Rated life time L80/B10 at 25 °C 72000

BL ONE Comfort 1300 >80



BL ONE Comfort LED strip 1220lm/m 24VDC 9.1W/m IP20 827 20m

Technical INFORMATION

State of origin	AT
Customs tariff number	9405423990
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	20000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON LEDON Technology. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at