


BL ONE Comfort 1300 >80

BL ONE Comfort LED strip 1310lm/m 24VDC 9.1W/m IP20 840 5m

Article no.: 100182




Lamp voltage



Max. length



Colour rendering index CRI




Luminous flux per meter

TENDER TEXT

LED strip ONE Comfort 1310 lm/m 24VDC 9.1W/m 144lm/W IP20 CRI>80 4000K, one-sided connection cable 50 cm, WHITE 5 meter LED module BL ONE Comfort 1300 >80 Article 100182 Linear LED light strip IC-controlled on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Comfort 1300 >80 LED-strip has a luminous flux of 1310 at 9.1 , resulting in an efficiency of 144 . At a nominal voltage of 24 DC on the connection, a maximum module length of 7500 can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 . Dimension (L x W x H): 5000 x 8 x 1.5

TOP-FEATURES

- //__ Wide range of lumens and light colours
- //__ Maximum homogeneity thanks to 140 LEDs per metre
- //__ Economical energy consumption
- //__ Produced in Austria



BL ONE Comfort 1300 >80

BL ONE Comfort LED strip 1310lm/m 24VDC 9.1W/m IP20 840 5m

Article no.: 100182



MECHANICAL DATA

Width	8
Length	5000
Height/depth	1.5
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments	50
Lowest bending radius	20
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	9.1
Overall efficiency	144

LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>80
Colour temperature [K]	4000
Colour of light	neutral white
Luminous flux per meter	1310
Energy efficiency class provided exchangeable built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	7500

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	0 ... + 60
Operation temperature at Tc	- 5 ... + 60

Ambient temperature during operating -20 +45
Rated life time L80/B10 at 25 °C 60000

BL ONE Comfort 1300 >80



BL ONE Comfort LED strip 1310lm/m 24VDC 9.1W/m IP20 840 5m

PACKAGING INFORMATION

State of origin	AT
Customs tariff number	9405423990
Net weight [g]	68
Gross weight [g]	110
Gross width [mm]	220
Gross height [mm]	10
Gross length [mm]	260
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 °C ambient temperature under the standardized measuring environment of BILTON LEDON Technology. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at