


BL ONE Comfort 1000 >90

BL ONE Comfort LED strip 965lm/m 24VDC 8.6W/m IP20 930 20m

Article no.: 100162



24

Lamp voltage

7500

Max. length

>90

Colour rendering index CRI

965

Luminous flux per meter

TENDER TEXT

LED strip ONE Comfort 965 lm/m 24VDC 8.6W/m 112lm/W IP20 CRI>90 3000K, without connection cable, WHITE 20 meter LED module BL ONE Comfort 1000 >90 Article 100162 Linear LED light strip IC-controlled on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Comfort 1000 >90 LED-strip has a luminous flux of 965 at 8.6 , resulting in an efficiency of 112 . At a nominal voltage of 24 DC on the connection, a maximum module length of 7500 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 . Dimension (L x W x H): 20000 x 8 x 1.5

TOP-FEATURES

- //__ Wide range of lumens and light colours
- //__ Maximum homogeneity thanks to 140 LEDs per metre
- //__ Economical energy consumption
- //__ Produced in Austria



BL ONE Comfort 1000 >90

BL ONE Comfort LED strip 965lm/m 24VDC 8.6W/m IP20 930 20m

Article no.: 100162



PACKAGING INFORMATION

State of origin	AT
Customs tariff number	9405423990
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	20000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON LEDON Technology. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at