

# BL ONE Comfort 1000 >80

BL ONE Comfort LED strip 980lm/m 24VDC 7.1W/m IP20 830 5m


Article no.: 100141



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

LED strip ONE Comfort 980 lm/m 24VDC 7.1W/m 138lm/W IP20 CRI>80 3000K, one-sided connection cable 50 cm, WHITE 5 meter LED module BL ONE Comfort 1000 >80 Article 100141 Linear LED light strip IC-controlled on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 72000 . The BL ONE Comfort 1000 >80 LED-strip has a luminous flux of 980 at 7.1 , resulting in an efficiency of 138 . At a nominal voltage of 24 DC on the connection, a maximum module length of 9000 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 . Dimension (L x W x H): 5000 x 8 x 1.5

## TOP-FEATURES

- //\_\_ Wide range of lumens and light colours
- //\_\_ Maximum homogeneity thanks to 140 LEDs per metre
- //\_\_ Economical energy consumption
- //\_\_ Produced in Austria



# BL ONE Comfort 1000 >80

**BL ONE Comfort LED strip 980lm/m 24VDC 7.1W/m IP20 830 5m**

Article no.: 100141



## PACKAGING INFORMATION

State of origin	AT
Customs tariff number	9405423990
Net weight [g]	68
Gross weight [g]	110
Gross width [mm]	220
Gross height [mm]	10
Gross length [mm]	260
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON LEDON Technology. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)