


# BL ONE Select High-E 1300

BL ONE Select High-E LED strip 1220lm/m 24VDC 7.6W/m IP20 927 5m  
Article no.: 102155



Lamp voltage



Max. length



Colour rendering index CRI




Luminous flux per meter

## TENDER TEXT

LED strip High Efficiency 1220 lm/m 24VDC, 7.6 W/m, 161 lm/W, IP20, CRI>90, 2700K, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select High-E 1300 Article 102155 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select High-E 1300 LED-strip has a luminous flux of 1220 at 7.6 , resulting in an efficiency of 161 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5000 can be achieved. In terms of lighting, the module has a colour temperature of 2700 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 6.25 . Degree of protection IP20 Dimension (L x W x H): 5000 mm x 8 mm x 1.5 mm

## TOP-FEATURES

- //\_\_ Improvement of homogeneity by 20 additional LEDs per meter
- //\_\_ Wide choice of light colors and lumen packages
- //\_\_ Wide range of applications for linear lighting in white
- //\_\_ With a maximum module length of up to 5000 long, linear lighting lines can be implemented



# BL ONE Select High-E 1300

BL ONE Select High-E LED strip 1220lm/m 24VDC 7.6W/m IP20 927 5m

Article no.: 102155



## MECHANICAL DATA

Width [mm]	8
Length [mm]	5000
Height/depth	1.5
Height [mm]	1.5
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance	6.25
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments	50
Lowest bending radius	20
Number of lamps per meter	160

## ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	7.6
Overall efficiency	161

## LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>90
Colour temperature	2700
Colour of light	White
Luminous flux per meter	1220
Energy efficiency class provided exchangeable built-in lamp	D
Colour consistency (McAdam ellipse)	SDCM3

## CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	5000

# TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 5 ... + 55
<b>BL ONE Select High-E LED strip 1220lm/m 24VDC 7.6W/m IP20 927 5m</b>	
Operation temperature at T <sub>c</sub>	- 5 ... + 60
Article no.: 102155	
Ambient temperature during operating	- 20 ... + 45
Rated life time L80/B10 at 25 °C	60000



## PACKAGING INFORMATION

State of origin	AT
Customs tariff number	85395100
Net weight [g]	50
Gross weight [g]	175
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)