


# BL ONE Select High-E 3000

**BL ONE Select High-E LED strip 3000lm/m 24VDC 17.1W/m IP20 940 5m**


Article no.: 102163



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

LED strip High Efficiency 3000 lm/m 24VDC, 17.1 W/m, 175 lm/W, IP20, CRI>90, 4000K, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select High-E 3000 Article 102163 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select High-E 3000 LED-strip has a luminous flux of 3000 at 17.1 , resulting in an efficiency of 175 . At a nominal voltage of 24 DC on the connection, a maximum module length of 3000 can be achieved. In terms of lighting, the module has a colour temperature of 4000 and a beam angle of 120 . All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 6.25 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 mm x 1.5

## TOP-FEATURES

//\_\_ Improvement of homogeneity by 20 additional LEDs per meter

//\_\_ Wide choice of light colors and lumen packages

//\_\_ Wide range of applications for linear lighting in white

//\_\_ With a maximum module length of up to 3000 long, linear lighting lines can be implemented



# BL ONE Select High-E 3000

**BL ONE Select High-E LED strip 3000lm/m 24VDC 17.1W/m IP20 940 5m**

Article no.: 102163



## MECHANICAL DATA

Width [mm]	8
Length	5000
Height/depth	1.5
Height	1.5
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance	6.25
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments	50
Lowest bending radius	20
Number of lamps per meter	160

## ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage	24
Input voltage range	23 - 25
Lamp power per meter	17.1
Overall efficiency	175

## LIGHT TECHNICAL DATA

Beam angle	120
Colour rendering index CRI	>90
Colour temperature	4000
Colour of light	White
Luminous flux per meter	3000
Energy efficiency class provided exchangeable built-in lamp	C
Colour consistency (McAdam ellipse)	SDCM3

## CONNECTION

Conductor cross section	0.5
Number of poles	2
Max. length	3000

## TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 5 ... + 55
-----------------------------	--------------

Operation temperature at  $T_c$   
Ambient temperature during operating

5 ... +60  
20 ... +45

Rated life time 180,000h at 25 °C  
BL ONE Select High-E LED strip 3000lm/m 24VDC 17.1W/m IP20 940 5m

Article no.: 102163

## PACKAGING INFORMATION

State of origin	AT
Customs tariff number	85395100
Net weight [g]	50
Gross weight [g]	175
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 °C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)

