


BL ONE Select Retail 1300

BL ONE Select Retail LED strip 1130lm/m 24VDC 11.5W/m IP20 930 5m

Article no.: 101814



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED strip ONE Select Retail 1130 lm/m 24VDC, 11.5W/m, 98 lm/W, IP20, CRI>95, 3000K, WHITE, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select Retail 1300 Article 101814 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select Retail 1300 LED-strip has a luminous flux of 1130 at 11.5 , resulting in an efficiency of 98 . At a nominal voltage of 24 DC on the connection, a maximum module length of 7500 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >95 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 x 1.5

TOP-FEATURES

- //__ Best light quality for shop lighting thanks to CRI >95
- //__ Long line lengths and better stability due to double layer
- //__ Wide choice of light colors and lumen packages
- //__ Available in Degree of Protection IP20



PACKAGING INFORMATION

BL ONE Select Retail 1300

State of origin AT
BL ONE Select Retail LED strip 1130lm/m 24VDC 11.5W/m IP20 930 5m
Customs tariff number 94054099
Article no.: 101814
Net weight [g] 0.049



Gross weight [g]	0.049
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at