


BL ONE Select Retail 2000

BL ONE Select Retail LED strip 1740lm/m 24VDC 17.9W/m IPX6 930 5m
Article no.: 101832



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED strip ONE Select Retail 1740 lm/m 24VDC, 17.9W/m, 97 lm/W, IPX6, CRI>95, 3000K, WHITE, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select Retail 2000 Article 101832 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select Retail 2000 LED-strip has a luminous flux of 1740 at 17.9 , resulting in an efficiency of 97 . At a nominal voltage of 24 DC on the connection, a maximum module length of 5500 can be achieved. In terms of lighting, the module has a colour temperature of 3000 and a beam angle of 120 . All this with a colour rendering index of >95 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IPX6 Dimension (L x W x H): 5000 x 8 x 1.5

TOP-FEATURES

- //__ Best light quality for shop lighting thanks to CRI >95
- //__ Long line lengths and better stability due to double layer
- //__ Wide choice of light colors and lumen packages
- //__ Available in Degree of Protection IPX6



PACKAGING INFORMATION

BL ONE Select Retail 2000

State of origin AT
BL ONE Select Retail LED strip 1740lm/m 24VDC 17.9W/m IPX6 930 5m
Customs tariff number 94054099
Article no.: 101832
Gross width [mm] 200



Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at