


# BL ONE Select SOL

BL ONE Select SOL LED strip 3000lm/m 24VDC 29W/m IP20 FS 4000K 5m

Article no.: 100005



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

LED strip ONE Select SOL 3000 lm/m 24VDC 29W/m 103lm/W IP20 CRI>98 4000K WHITE, separability 50mm, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select SOL Article 100005 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select SOL LED-strip has a luminous flux of 3000 at 29 , resulting in an efficiency of 103 . At a nominal voltage of 24 DC on the connection, a maximum module length of 4000 can be achieved. In terms of lighting, the module has a colour temperature of 4000 and a beam angle of 120 . All this with a colour rendering index of >98 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 Dimension (L x W x H): 5000 x 8 x 1.5

## TOP-FEATURES

//\_\_ LED strips for light close to sunlight due to very high CRI

//\_\_ For exceptional applications where natural light is needed.



# BL ONE Select SOL

**BL ONE Select SOL LED strip 3000lm/m 24VDC 29W/m IP20 FS 4000K 5m**

Article no.: 100005



## PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054099
Net weight [g]	49
Gross weight [g]	175
Gross width [mm]	200
Gross height [mm]	18
Gross length [mm]	200
Net width [mm]	8
Net height [mm]	1.5
Net length [mm]	5000

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)