


BL ONE Select XL 5000 >80

BL ONE Select XL LED strip 4700lm/m 24VDC 36.5W/m IP20 827 5m

Article no.: 101913



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED strip ONE Select XL 4700 lm/m 24VDC, 36.5W/m, 129 lm/W, IP20, CRI>80, 2700K, WHITE, module width 12 mm, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select XL 5000 >80 Article 101913 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 at a service life of 60000 . The BL ONE Select XL 5000 >80 LED-strip has a luminous flux of 4700 at 36.5 , resulting in an efficiency of 129 . At a nominal voltage of 24 DC on the connection, a maximum module length of 4000 can be achieved. In terms of lighting, the module has a colour temperature of 2700 and a beam angle of 120 . All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50 , resulting in a LED distance of 7.14 . Degree of protection IP20 Dimension (L x W x H): 5000 x 12 x 1.5

TOP-FEATURES

//__ High lumen packages up to 4700

//__ Module width of 12 for thermal conduction and long line lengths

//__ High design freedom, current capacity and longer module lengths are achievable



BL ONE Select XL 5000 >80

BL ONE Select XL LED strip 4700lm/m 24VDC 36.5W/m IP20 827 5m

Article no.: 101913



PACKAGING INFORMATION

State of origin	AT
Customs tariff number	94054099
Gross width [mm]	200
Gross height [mm]	22
Gross length [mm]	200
Net width [mm]	12
Net height [mm]	1.5
Net length [mm]	5000

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 °C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at