
BL Panel Comfort

BL Panel Comfort 620mm 3800lm 30W 90D 930 white 900mA

Article no.: 710112













TENDER TEXT

LED panel, 3,800 lumen, 30W, 90° direct beam, CRI >90, 3,000 Kelvin, IP20, protection class III, dimmable, UGR BL Panel Comfort Article 710112 LED panel for installation as Surface / Installation / Suspension - made of high-quality, White coated frames made of Aluminium . Microprismatic layer for modular ceilings with concealed or visible support system. Very flat and compact design with a total height of 10 . Best light quality with precise glare control 90 ; light color White , color temperature 3000 ; beam angle 90 , mounting set for Surface / Installation / Suspension must be ordered separately. Dimensions (L x W x H): 620 x 620 x 10

TOP-FEATURES

//__ LED panel light with microprismatic layer for modular ceilings with concealed or visible support system

//_ Best light quality with precise glare control and homogeneous light distribution over the entire light emission surface

//__ Glare limitation (UGR) <19











BL Panel Comfort

BL Panel Comfort 620mm 3800lm 30W 90D 930 white 900mA

Article no.: 710112



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width	620
Length	620
Height/depth	10
Mounting method	Surface / Installation / Suspension
With movement sensor	nein
Lamp type	LED nicht austauschbar
Material of the cover	Plastic structured
Degree of protection (IP)	IP20
Control gear included	nein
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage	29,9 - 36,6
Overall efficiency	127
Max. system power	30

LIGHT TECHNICAL DATA

Beam angle	90
Colour rendering index CRI	>90
Light exit	direkt
Rated luminous flux according to IEC 62722-2-1	3800
Colour temperature	3000
Colour of light	White
Energy efficiency class of teh built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM4

TEMPERATURE TECHNICAL DATA

Rated life time L80/B50 at 25 °C 50000

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	94054239
Net weight [g]	2480
Gross weight [g]	5000
Gross width [mm]	655

Gross height [mm] BLander annel Comfort	62	
Gross-length [Mm] ET COTTIOIL	665	
Bet Parte Comfort 620mm 3800lm 30W 90D	930 white 900mA	
Neticeishtd::ייסור איניים אינ	10	
Net length [mm]	620	BETTER LIGHT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at