


BL Panel Protected

BL Panel Protected 620mm 3750lm 32W 60D 840 white IP54

Article no.: 713005



Beam angle



Degree of protection (IP)



Rated luminous flux
according to IEC
62722-2-1

TENDER TEXT

LED panel, 3,750 lumen, 32W, 60° direct beam, CRI >80, 4,000 Kelvin, IP54, protection class II, non-dimmable, UGR BL Panel Protected Article 713005 LED panel for installation as Surface / Installation / Suspension - made of high-quality, White coated frames made of Aluminium . Microprismatic layer for modular ceilings with concealed or visible support system. Very flat and compact design with a total height of 10 . Homogeneous light distribution across the entire light emission surface, service life of 50000 , luminous flux 3750 ; Current max. , color rendering >80 ; light color White , color temperature 4000 ; UGR

TOP-FEATURES

//__ Very flat and compact design with a total height of 10

//__ Best light quality with precise glare control thanks to UGR <19

//__ Suitable for particularly demanding environments, thanks to IP54 protection class



BL Panel Protected

BL Panel Protected 620mm 3750lm 32W 60D 840 white IP54

Article no.: 713005



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width	620
Length	620
Height/depth	10
Mounting method	Surface / Installation / Suspension
With movement sensor	nein
Material of the cover	Plastic opal
Degree of protection (IP)	IP54
With lamp	yes
Control gear included	yes
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	II
Voltage type	AC
Nominal voltage	200 - 240
Operating frequency	50 / 60
Overall efficiency	100
Max. system power	32

LIGHT TECHNICAL DATA

Beam angle	60
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1	3750
Colour temperature	4000
Colour of light	White
Energy efficiency class of the built-in lamp	F

TEMPERATURE TECHNICAL DATA

Rated life time L70/B10 at 25 °C	50000
----------------------------------	-------

PACKAGING INFORMATION

State of origin	CN
Net weight [g]	2700
Gross weight [g]	3200
Net width [mm]	620

Net height [mm]
Net length [mm]

BL Panel Protected

10
620



BL Panel Protected 620mm 3750lm 32W 60D 840 white IP54

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at