

# Power Supply DALI Downlight

**BL TCI Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI**

Article no.: 729026




---

## TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 10-49VDC. Output current 350mA. DALI control signal. Protection class IP20. Protection class II. Dimensions LxWxH = 108x52x22mm

---



# Power Supply DALI Downlight

**BL TCI Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI**

Article no.: 729026



## MECHANICAL DATA

Width	52
Length	108
Height	22
Control signal	DALI
Degree of protection (IP)	IP20
Core cross section	0,5 - 1,5

## ELECTRICAL DATA

Protection class	III
Voltage type	AC
Control signal	DALI
Input voltage range	220 - 240
Output power range	12,5
Frequency supply voltage (range)	50 - 60
Output current range	72
Dimming DALI	yes

## CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

## TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C	50000
-------------------	-------

## PACKAGING INFORMATION

State of origin	IT
Net weight [g]	106
Gross weight [g]	106

**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)